



Safety data sheet according to UK REACH

Printing date 15.05.2025

Version number 6 (replaces version 5)

Revision: 15.05.2025

SECTION 1: Identification of the substance/mixture and of the company/undertaking

- **1.1 Product identifier**
- **Trade name:** **JOHA Volatile oil varnish**
- **Article number:** 2310 primer, 2320 color varnish colorless, 2330 coating
- **1.2 Relevant identified uses of the substance or mixture and uses advised against**
No further relevant information available.
- **Application of the substance / the mixture** For laquering a instrument.
- **1.3 Details of the supplier of the safety data sheet**
- **Manufacturer/Supplier:**
Hammerl GmbH & Co. KG
Geigenlacke / Violin varnishes
Hauptstraße 18
91083 Baiersdorf
Phone +49 (0)9133 2330
Fax +49 (0)9133 5171
e-mail joha@hammerl.com
- **1.4 Emergency telephone number:**
Giftinformationszentrale Universitätsklinikum Mainz
International
24h Emergency number in German and English
Phone: +49 6131 19240

SECTION 2: Hazards identification

- **2.1 Classification of the substance or mixture**
- **Classification according to Regulation (EC) No 1272/2008**



GHS02 flame

Flam. Liq. 3 H226 Flammable liquid and vapour.



GHS07

STOT SE 3 H336 May cause drowsiness or dizziness.

- **2.2 Label elements**
- **Labelling according to Regulation (EC) No 1272/2008**
The product is classified and labelled according to the GB CLP regulation.
- **Hazard pictograms**



GHS02 GHS07

- **Signal word** Warning
- **Hazard-determining components of labelling:**
1-methoxy-2-propanol
- **Hazard statements**
H226 Flammable liquid and vapour.
H336 May cause drowsiness or dizziness.

(Contd. on page 2)



Safety data sheet according to UK REACH

Printing date 15.05.2025

Version number 6 (replaces version 5)

Revision: 15.05.2025

Trade name: JOHA Volatile oil varnish

(Contd. of page 1)

Precautionary statements

- P101 If medical advice is needed, have product container or label at hand.
P102 Keep out of reach of children.
P103 Read carefully and follow all instructions.
P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
P241 Use explosion-proof [electrical/ventilating/lighting] equipment.
P261 Avoid breathing dust/fume/gas/mist/vapours/spray.
P303+P361+P353 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water [or shower].
P405 Store locked up.
P501 Dispose of contents/container in accordance with local/regional/national/international regulations.

Additional information:

22.6 % of the mixture consists of component(s) of unknown toxicity.

2.3 Other hazards**Results of PBT and vPvB assessment****PBT:** Not applicable.**vPvB:** Not applicable.

SECTION 3: Composition/information on ingredients

3.2 Mixtures**Description:** Mixture of substances listed below with nonhazardous additions.**Dangerous components:**

CAS: 107-98-2 EINECS: 203-539-1	1-methoxy-2-propanol Flam. Liq. 3, H226 STOT SE 3, H336	50-99%
CAS: 64-17-5 EINECS: 200-578-6	ethanol Flam. Liq. 2, H225	10-25%
CAS: 8006-64-2 EINECS: 232-350-7	Turpentine, oil Flam. Liq. 3, H226 Asp. Tox. 1, H304 Aquatic Chronic 2, H411 Acute Tox. 4, H302; Acute Tox. 4, H312; Acute Tox. 4, H332; Skin Irrit. 2, H315; Eye Irrit. 2, H319; Skin Sens. 1, H317	≥0.25-<1%
CAS: 78-93-3 EINECS: 201-159-0	butanone Flam. Liq. 2, H225 Eye Irrit. 2, H319; STOT SE 3, H336 EUH066	≤2.5%

Additional information: For the wording of the listed hazard phrases refer to section 16.

SECTION 4: First aid measures

4.1 Description of first aid measures**After inhalation:** Supply fresh air; consult doctor in case of complaints.**After skin contact:** Immediately rinse with water.**After eye contact:** Rinse opened eye for several minutes under running water.**After swallowing:** If symptoms persist consult doctor.**4.2 Most important symptoms and effects, both acute and delayed**

No further relevant information available.

(Contd. on page 3)



Safety data sheet according to UK REACH

Printing date 15.05.2025

Version number 6 (replaces version 5)

Revision: 15.05.2025

Trade name: JOHA Volatile oil varnish

(Contd. of page 2)

- **4.3 Indication of any immediate medical attention and special treatment needed**
No further relevant information available.

SECTION 5: Firefighting measures

- **5.1 Extinguishing media**
- **Suitable extinguishing agents:**
CO₂, powder or water spray. Fight larger fires with water spray or alcohol resistant foam.
- **For safety reasons unsuitable extinguishing agents:** Water with full jet
- **5.2 Special hazards arising from the substance or mixture**
No further relevant information available.
- **5.3 Advice for firefighters**
- **Protective equipment:** No special measures required.

SECTION 6: Accidental release measures

- **6.1 Personal precautions, protective equipment and emergency procedures**
Wear protective equipment. Keep unprotected persons away.
- **6.2 Environmental precautions:** Do not allow to enter sewers/ surface or ground water.
- **6.3 Methods and material for containment and cleaning up:**
Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).
Dispose contaminated material as waste according to section 13.
Ensure adequate ventilation.
- **6.4 Reference to other sections**
See Section 7 for information on safe handling.
See Section 8 for information on personal protection equipment.
See Section 13 for disposal information.

SECTION 7: Handling and storage

- **7.1 Precautions for safe handling**
Ensure good ventilation/exhaustion at the workplace.
Prevent formation of aerosols.
- **Information about fire - and explosion protection:**
Keep ignition sources away - Do not smoke.
Protect against electrostatic charges.
- **7.2 Conditions for safe storage, including any incompatibilities**
- **Storage:**
- **Requirements to be met by storerooms and receptacles:** No special requirements.
- **Information about storage in one common storage facility:** Not required.
- **Further information about storage conditions:** Keep container tightly sealed.
- **7.3 Specific end use(s)** No further relevant information available.

GB

(Contd. on page 4)



Safety data sheet according to UK REACH

Printing date 15.05.2025

Version number 6 (replaces version 5)

Revision: 15.05.2025

Trade name: JOHA Volatile oil varnish

(Contd. of page 3)

SECTION 8: Exposure controls/personal protection

8.1 Control parameters

Ingredients with limit values that require monitoring at the workplace:

107-98-2 1-methoxy-2-propanol

WEL	Short-term value: 560 mg/m ³ , 150 ppm
	Long-term value: 375 mg/m ³ , 100 ppm
Sk	

64-17-5 ethanol

WEL	Long-term value: 1920 mg/m ³ , 1000 ppm
-----	--

8006-64-2 Turpentine, oil

WEL	Short-term value: 850 mg/m ³ , 150 ppm
	Long-term value: 566 mg/m ³ , 100 ppm

78-93-3 butanone

WEL	Short-term value: 899 mg/m ³ , 300 ppm
	Long-term value: 600 mg/m ³ , 200 ppm
Sk, BMGV	

Ingredients with biological limit values:

78-93-3 butanone

BMGV	70 µmol/L
	Medium: urine
	Sampling time: post shift
	Parameter: butan-2-one

Additional information: The lists valid during the making were used as basis.

8.2 Exposure controls

Appropriate engineering controls No further data; see section 7.

Individual protection measures, such as personal protective equipment

General protective and hygienic measures:

Immediately remove all soiled and contaminated clothing

Wash hands before breaks and at the end of work.

Respiratory protection:

In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use self-contained respiratory protective device.

Hand protection



Protective gloves

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.

Due to missing tests no recommendation to the glove material can be given for the product/ the preparation/ the chemical mixture.

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

Material of gloves

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

(Contd. on page 5)

GB

**Safety data sheet
according to UK REACH**

Printing date 15.05.2025

Version number 6 (replaces version 5)

Revision: 15.05.2025

Trade name: JOHA Volatile oil varnish

(Contd. of page 4)

· Penetration time of glove material

The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.

· Eye/face protection

Tightly sealed goggles

*

SECTION 9: Physical and chemical properties**· 9.1 Information on basic physical and chemical properties****· General Information****· Physical state**

Liquid

· Colour:

According to product specification

· Odour:

Characteristic

· Odour threshold:

Not determined.

· Melting point/freezing point:

Undetermined.

· Boiling point or initial boiling point and boiling range

78 °C

· Flammability

Flammable.

· Lower and upper explosion limit**· Lower:**

2.3 Vol %

· Upper:

20 Vol %

· Flash point:

32 °C

· Auto-ignition temperature:

270 °C (DIN 51794)

· Decomposition temperature:

Not determined.

· pH

Not determined.

· Viscosity:**· Kinematic viscosity**

Not determined.

· Dynamic:

Not determined.

· Solubility**· water:**

Not miscible or difficult to mix.

· Partition coefficient n-octanol/water (log value)

Not determined.

· Vapour pressure at 20 °C:

59 hPa

· Density and/or relative density**· Density:**

Not determined.

· Relative density

Not determined.

· Vapour density

Not determined.

· 9.2 Other information**· Appearance:****· Form:**

Fluid

· Important information on protection of health and environment, and on safety.**· Ignition temperature:**

Product is not selfigniting.

· Explosive properties:

Product is not explosive. However, formation of explosive air/vapour mixtures are possible.

· Solvent content:**· Organic solvents:**

76.5 %

· Solids content:

22.4 %

(Contd. on page 6)

GB

**Safety data sheet
according to UK REACH**

Printing date 15.05.2025

Version number 6 (replaces version 5)

Revision: 15.05.2025

Trade name: JOHA Volatile oil varnish

(Contd. of page 5)

· Change in condition**· Evaporation rate** Not determined.**· Information with regard to physical hazard classes**

· Explosives	Void
· Flammable gases	Void
· Aerosols	Void
· Oxidising gases	Void
· Gases under pressure	Void
· Flammable liquids	Flammable liquid and vapour.
· Flammable solids	Void
· Self-reactive substances and mixtures	Void
· Pyrophoric liquids	Void
· Pyrophoric solids	Void
· Self-heating substances and mixtures	Void
· Substances and mixtures, which emit flammable gases in contact with water	Void
· Oxidising liquids	Void
· Oxidising solids	Void
· Organic peroxides	Void
· Corrosive to metals	Void
· Desensitised explosives	Void

SECTION 10: Stability and reactivity

- **10.1 Reactivity** No further relevant information available.
- **10.2 Chemical stability**
- **Thermal decomposition / conditions to be avoided:**
No decomposition if used according to specifications.
- **10.3 Possibility of hazardous reactions** No dangerous reactions known.
- **10.4 Conditions to avoid** No further relevant information available.
- **10.5 Incompatible materials:** No further relevant information available.
- **10.6 Hazardous decomposition products:** No dangerous decomposition products known.

*

SECTION 11: Toxicological information

- **11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008**
- **Acute toxicity** Based on available data, the classification criteria are not met.

· LD/LC50 values relevant for classification:**107-98-2 1-methoxy-2-propanol**

Oral	LD50	4,016 mg/kg (rat)
Dermal	LD50	13,000 mg/kg (rabbit)

64-17-5 ethanol

Oral	LD50	3,450 mg/kg (mouse) 7,060 mg/kg (rat) 6,300 mg/kg (rabbit)
Dermal	LD50	>2,000 mg/kg (rat)
Inhalative	LC50/4 h	20,000 mg/l (rat)

- **STOT-single exposure** May cause drowsiness or dizziness.

(Contd. on page 7)

GB

**Safety data sheet
according to UK REACH**

Printing date 15.05.2025

Version number 6 (replaces version 5)

Revision: 15.05.2025

Trade name: JOHA Volatile oil varnish

(Contd. of page 6)

11.2 Information on other hazards**Endocrine disrupting properties**

78-93-3 butanone

List II

*

SECTION 12: Ecological information**12.1 Toxicity****Aquatic toxicity:** No further relevant information available.**Type of test Effective concentration Method Assessment****107-98-2 1-methoxy-2-propanol**

LC50 (48h)	23,300 mg/l (daphnia magna)
LC50 (96h)	>6,800 mg/l (gol)
EC50 (3h)	>1,000 mg/l (Pseudomonas Putita)

64-17-5 ethanol

EC50 (48h)	9,268 mg/l (daphnia magna)
LC50 (48h)	8,140 mg/l (gol)
LC50 (24h)	>100 mg/l (daphnia magna)
EC5 (16h)	6,500 mg/l (Pseudomonas Putita)

12.2 Persistence and degradability No further relevant information available.**12.3 Bioaccumulative potential** No further relevant information available.**12.4 Mobility in soil** No further relevant information available.**12.5 Results of PBT and vPvB assessment****PBT:** Not applicable.**vPvB:** Not applicable.**12.6 Endocrine disrupting properties**

For information on endocrine disrupting properties see section 11.

12.7 Other adverse effects**Additional ecological information:****General notes:**

Water hazard class 1 (German Regulation) (Self-assessment): slightly hazardous for water
Do not allow undiluted product or large quantities of it to reach ground water, water course or sewage system.

SECTION 13: Disposal considerations**13.1 Waste treatment methods****Recommendation**

Must not be disposed together with household garbage. Do not allow product to reach sewage system.

Uncleaned packaging:**Recommendation:** Disposal must be made according to official regulations.

*

SECTION 14: Transport information**14.1 UN number or ID number****ADR, IMDG, IATA**

UN1170

(Contd. on page 8)

GB

**Safety data sheet
according to UK REACH**

Printing date 15.05.2025

Version number 6 (replaces version 5)

Revision: 15.05.2025

Trade name: JOHA Volatile oil varnish

(Contd. of page 7)

· 14.2 UN proper shipping name**· ADR**

1170 ETHANOL (ETHYL ALCOHOL)

· IMDG

ETHANOL (ETHYL ALCOHOL)

· IATA

ETHANOL

· 14.3 Transport hazard class(es)**· ADR, IMDG, IATA****· Class**

3 Flammable liquids.

· Label

3

· 14.4 Packing group**· ADR, IMDG, IATA**

III

· 14.5 Environmental hazards:**· Marine pollutant:**

No

· 14.6 Special precautions for user

Warning: Flammable liquids.

· Hazard identification number (Kemler code):

30

· EMS Number:

F-E, S-D

· Stowage Category

A

· 14.7 Maritime transport in bulk according to IMO instruments

Not applicable.

· Transport/Additional information:**· ADR****· Limited quantities (LQ)**

5L

· Excepted quantities (EQ)

Code: E1

Maximum net quantity per inner packaging: 30 ml

Maximum net quantity per outer packaging: 1000 ml

· Transport category

3

· Tunnel restriction code

D/E

· IMDG**· Limited quantities (LQ)**

5L

· Excepted quantities (EQ)

Code: E1

Maximum net quantity per inner packaging: 30 ml

Maximum net quantity per outer packaging: 1000 ml

· UN "Model Regulation":

UN 1170 ETHANOL (ETHYL ALCOHOL), 3, III

GB

(Contd. on page 9)



Safety data sheet according to UK REACH

Printing date 15.05.2025

Version number 6 (replaces version 5)

Revision: 15.05.2025

Trade name: JOHA Volatile oil varnish

(Contd. of page 8)

SECTION 15: Regulatory information

· 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

· Poisons Act

· Regulated explosives precursors

None of the ingredients is listed.

· Regulated poisons

None of the ingredients is listed.

· Reportable explosives precursors

None of the ingredients is listed.

· Reportable poisons

None of the ingredients is listed.

· Labelling according to Regulation (EC) No 1272/2008

The product is classified and labelled according to the GB CLP regulation.

· Hazard pictograms



GHS02 GHS07

· Signal word Warning

· Hazard-determining components of labelling:

1-methoxy-2-propanol

· Hazard statements

H226 Flammable liquid and vapour.

H336 May cause drowsiness or dizziness.

· Precautionary statements

P101 If medical advice is needed, have product container or label at hand.

P102 Keep out of reach of children.

P103 Read carefully and follow all instructions.

P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

P241 Use explosion-proof [electrical/ventilating/lighting] equipment.

P261 Avoid breathing dust/fume/gas/mist/vapours/spray.

P303+P361+P353 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water [or shower].

P405 Store locked up.

P501 Dispose of contents/container in accordance with local/regional/national/international regulations.

· Directive 2012/18/EU

· Named dangerous substances - ANNEX I None of the ingredients is listed.

· Seveso category P5c FLAMMABLE LIQUIDS

· Qualifying quantity (tonnes) for the application of lower-tier requirements 5,000 t

· Qualifying quantity (tonnes) for the application of upper-tier requirements 50,000 t

· National regulations:

· Additional classification according to Decree on Hazardous Materials, Annex II:

Carcinogenic hazardous material group III (dangerous).

· Waterhazard class: Water hazard class 1 (Self-assessment): slightly hazardous for water.

(Contd. on page 10)



Safety data sheet according to UK REACH

Printing date 15.05.2025

Version number 6 (replaces version 5)

Revision: 15.05.2025

Trade name: JOHA Volatile oil varnish

(Contd. of page 9)

15.2 Chemical safety assessment:

A Chemical Safety Assessment has not been carried out.

SECTION 16: Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

Relevant phrases

- H225 Highly flammable liquid and vapour.
- H226 Flammable liquid and vapour.
- H302 Harmful if swallowed.
- H304 May be fatal if swallowed and enters airways.
- H312 Harmful in contact with skin.
- H315 Causes skin irritation.
- H317 May cause an allergic skin reaction.
- H319 Causes serious eye irritation.
- H332 Harmful if inhaled.
- H336 May cause drowsiness or dizziness.
- H411 Toxic to aquatic life with long lasting effects.
- EUH066 Repeated exposure may cause skin dryness or cracking.

Department issuing SDS: Abteilung Umweltschutz**Contact: Hr. Hammerl****Abbreviations and acronyms:**

- RID: Règlement international concernant le transport des marchandises dangereuses par chemin de fer (Regulations Concerning the International Transport of Dangerous Goods by Rail)
- ICAO: International Civil Aviation Organisation
- ADR: Accord relatif au transport international des marchandises dangereuses par route (European Agreement Concerning the International Carriage of Dangerous Goods by Road)
- IMDG: International Maritime Code for Dangerous Goods
- IATA: International Air Transport Association
- GHS: Globally Harmonised System of Classification and Labelling of Chemicals
- EINECS: European Inventory of Existing Commercial Chemical Substances
- ELINCS: European List of Notified Chemical Substances
- CAS: Chemical Abstracts Service (division of the American Chemical Society)
- LC50: Lethal concentration, 50 percent
- LD50: Lethal dose, 50 percent
- PBT: Persistent, Bioaccumulative and Toxic
- vPvB: very Persistent and very Bioaccumulative
- Flam. Liq. 2: Flammable liquids – Category 2
- Flam. Liq. 3: Flammable liquids – Category 3
- Acute Tox. 4: Acute toxicity – Category 4
- Skin Irrit. 2: Skin corrosion/irritation – Category 2
- Eye Irrit. 2: Serious eye damage/eye irritation – Category 2
- Skin Sens. 1: Skin sensitisation – Category 1
- STOT SE 3: Specific target organ toxicity (single exposure) – Category 3
- Asp. Tox. 1: Aspiration hazard – Category 1
- Aquatic Chronic 2: Hazardous to the aquatic environment - long-term aquatic hazard – Category 2

*** Data compared to the previous version altered.**