

Safety data sheet according to 1907/2006/EC, Article 31

Version number 4 Revision: 21.03.2017

SECTION 1: Identification of the substance/mixture and of the company/undertaking

- · 1.1 Product identifier
- · Trade name: JOHA Siccativ-Drying agent
- · Article number: 2601
- · 1.2 Relevant identified uses of the substance or mixture and uses advised against
- · Application of the substance / the mixture Drier/ Catalyst
- · 1.3 Details of the supplier of the safety data sheet
- · Manufacturer/Supplier:

Hammerl GmbH & Co. KG Geigenlacke / Violin varnishes Hauptstraße 18 91083 Baiersdorf

Phone +49 (0)9133 2330 Fax +49 (0)9133 5171

e-mail joha@hammerl.com

· 1.4 Emergency telephone number:

Giftinformationszentrale Universitätsklinikum Mainz International

24h Emergency number in German and English

Phone: +49 6131 19240

SECTION 2: Hazards identification

- · 2.1 Classification of the substance or mixture
- Classification according to Regulation (EC) No 1272/2008



GHS02 flame

Flam. Liq. 3 Flammable liquid and vapour. H226



GHS09 environment

Aquatic Chronic 2 H411 Toxic to aquatic life with long lasting effects.



GHS07

Skin Irrit. 2

H315

Causes skin irritation.

Eye Irrit. 2

H319

Causes serious eye irritation.

STOT SE 3

H335-H336 May cause respiratory irritation. May cause drowsiness or

dizziness.

- · 2.2 Label elements
- · Labelling according to Regulation (EC) No 1272/2008

The product is classified and labelled according to the CLP regulation.

(Contd. on page 2)



Safety data sheet according to 1907/2006/EC, Article 31

Printing date 21.03.2017 Version number 4 Revision: 21.03.2017

Trade name: JOHA Siccativ-Drying agent

(Contd. of page 1)

· Hazard pictograms







GHS02 GHS07 GHS09

· Signal word Warning

· Hazard-determining components of labelling:

Solvent naphtha (petroleum), light arom.

· Hazard statements

H226 Flammable liquid and vapour.

H315 Causes skin irritation.

H319 Causes serious eye irritation.

H335-H336 May cause respiratory irritation. May cause drowsiness or dizziness.

H411 Toxic to aquatic life with long lasting effects.

· Precautionary statements

P101 If medical advice is needed, have product container or label at hand.

P102 Keep out of reach of children.

P103 Read label before use.

P210 Keep away from heat, hot surfaces, sparks, open flames and other

ignition sources. No smoking.

P241 Use explosion-proof electrical/ventilating/lighting equipment.

P303+P361+P353 IF ON SKIN (or hair): Take off immediately all contaminated clothing.

Rinse skin with water/shower.

P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove

contact lenses, if present and easy to do. Continue rinsing.

P405 Store locked up.

P501 Dispose of contents/container in accordance with local/regional/national/

international regulations.

· Labelling of packages where the contents do not exceed 125 ml

· Hazard pictograms







GHS02 GHS07 GHS09

· Signal word Warning

· Hazard-determining components of labelling:

Solvent naphtha (petroleum), light arom.

· Hazard statements

H335-H336 May cause respiratory irritation. May cause drowsiness or dizziness.

· Precautionary statements

P101 If medical advice is needed, have product container or label at hand.

P102 Keep out of reach of children.

P103 Read label before use.

P261 Avoid breathing dust/fume/gas/mist/vapours/spray.

P304+P340 IF INHALED: Remove person to fresh air and keep comfortable for breathing.

P312 Call a POISON CENTER/doctor if you feel unwell.

P405 Store locked up.

P403+P233 Store in a well-ventilated place. Keep container tightly closed.

P501 Dispose of contents/container in accordance with local/regional/national/

international regulations.

(Contd. on page 3)

Trade name: JOHA Siccativ-Drying agent

(Contd. of page 2)

- · 2.3 Other hazards
- · Results of PBT and vPvB assessment
- PBT: Not applicable.vPvB: Not applicable.

SECTION 3: Composition/information on ingredients

- · 3.2 Chemical characterisation: Mixtures
- · **Description**: Mixture of substances listed below with nonhazardous additions.

· Dangerous compor	nents:	
	Solvent naphtha (petroleum), light arom. Flam. Liq. 3, H226 Asp. Tox. 1, H304 Aquatic Chronic 2, H411 STOT SE 3, H335-H336	25-50%
CAS: 64742-48-9 EINECS: 265-150-3	Naphtha (petroleum), hydrotreated heavy \$ Asp. Tox. 1, H304	10-25%
CAS: 95-63-6 EINECS: 202-436-9	1,2,4-trimethylbenzene Flam. Liq. 3, H226 Aquatic Chronic 2, H411 Acute Tox. 4, H332; Skin Irrit. 2, H315; Eye Irrit. 2, H319; STOT SE 3, H335	10-<25%
CAS: 108-67-8 EINECS: 203-604-4	mesitylene Flam. Liq. 3, H226 Aquatic Chronic 2, H411 STOT SE 3, H335	2.5-<10%
CAS: 103-65-1 EINECS: 203-132-9	propylbenzene Flam. Liq. 3, H226 Asp. Tox. 1, H304 Aquatic Chronic 2, H411 STOT SE 3, H335	2.5-<10%

· Additional information: For the wording of the listed hazard phrases refer to section 16.

SECTION 4: First aid measures

- · 4.1 Description of first aid measures
- · After inhalation:

In case of unconsciousness place patient stably in side position for transportation. Move victim to fresh air. Put victim at rest and keep warm. In case of irregular breathing or respiratory arrest provide artificial respiration.

· After skin contact:

Immediately wash with water and soap and rinse thoroughly.

Take off immediately all contaminated clothing. After contact with skin, wash immediately with plenty of water and soap. Do not use solvents or thinners.

· After eye contact:

Rinse opened eye for several minutes under running water. If symptoms persist, consult a doctor.

IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue

rinsing. Seek medical advice.

(Contd. on page 4)

Trade name: JOHA Siccativ-Drying agent

(Contd. of page 3)

· After swallowing:

If swallowed, rinse mouth with water (only if the person is conscious). Consult physician immediately. Keep victim calm. Do not induce vomiting.

- 4.2 Most important symptoms and effects, both acute and delayed No further relevant information available.
- 4.3 Indication of any immediate medical attention and special treatment needed No further relevant information available.

SECTION 5: Firefighting measures

- · 5.1 Extinguishing media
- · Suitable extinguishing agents: Alcohol resistant foam
- · For safety reasons unsuitable extinguishing agents: Water with full jet
- · 5.2 Special hazards arising from the substance or mixture

Dense black smoke occurs during fire. Inhaling hazardous decomposing products can cause serious health damage.

- · 5.3 Advice for firefighters
- · Protective equipment: Wear self-contained respiratory protective device.
- · Additional information

Cool closed containers that are near the source of the fire. Do not allow water used to extinguish fire to enter drains, ground or waterways. Treat runoff as hazardous.

SECTION 6: Accidental release measures

- 6.1 Personal precautions, protective equipment and emergency procedures Wear protective equipment. Keep unprotected persons away.
- · 6.2 Environmental precautions:

Do not allow product to reach sewage system or any water course.

Inform respective authorities in case of seepage into water course or sewage system.

Do not allow to enter sewers/ surface or ground water.

· 6.3 Methods and material for containment and cleaning up:

Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).

Dispose contaminated material as waste according to item 13.

Ensure adequate ventilation.

· 6.4 Reference to other sections

See Section 7 for information on safe handling.

See Section 8 for information on personal protection equipment.

See Section 13 for disposal information.

SECTION 7: Handling and storage

· 7.1 Precautions for safe handling

Ensure good ventilation/exhaustion at the workplace.

Prevent formation of aerosols.

· Information about fire - and explosion protection:

Keep ignition sources away - Do not smoke.

Protect against electrostatic charges.

(Contd. on page 5)

Trade name: JOHA Siccativ-Drying agent

(Contd. of page 4)

- · 7.2 Conditions for safe storage, including any incompatibilities
- · Storage:
- · Requirements to be met by storerooms and receptacles: No special requirements.
- · Information about storage in one common storage facility: Not required.
- · Further information about storage conditions: Keep container tightly sealed.
- · 7.3 Specific end use(s) No further relevant information available.

SECTION 8: Exposure controls/personal protection

- · Additional information about design of technical facilities: No further data; see item 7.
- · 8.1 Control parameters
- Ingredients with limit values that require monitoring at the workplace:

95-63-6 1,2,4-trimethylbenzene

WEL Long-term value: 125 mg/m³, 25 ppm

ILV

108-67-8 mesitylene

WEL Long-term value: 125 mg/m³, 25 ppm

ILV

- · Additional information: The lists valid during the making were used as basis.
- · 8.2 Exposure controls
- · Personal protective equipment:
- · General protective and hygienic measures:

Keep away from foodstuffs, beverages and feed.

Immediately remove all soiled and contaminated clothing

Wash hands before breaks and at the end of work.

Avoid contact with the eyes and skin.

· Respiratory protection:

In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use self-contained respiratory protective device.

· Protection of hands:



Protective gloves

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.

Due to missing tests no recommendation to the glove material can be given for the product/ the preparation/ the chemical mixture.

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

· Material of gloves

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

· Penetration time of glove material

The exact break trough time has to be found out by the manufacturer of the protective gloves and has to be observed.

(Contd. on page 6)


(Contd. of page 5)



Printing date 21.03.2017 Version number 4 Revision: 21.03.2017

Trade name: JOHA Siccativ-Drying agent

· Eye protection:



SECTION 9: Physical and chemical properties

· 9.1 Information on basic physical and chemical properties

· General Information

· Appearance:

Form:

Fluid

Colour:

According to product specification

· Odour:

Characteristic

· Odour threshold:

Not determined.

· pH-value:

Not determined.

· Change in condition

Melting point/freezing point:

Undetermined.

Initial boiling point and boiling range: 162 °C

· Flash point:

24 °C

· Flammability (solid, gas):

Not applicable.

· Ignition temperature:

240 °C

· Decomposition temperature:

Not determined.

· Auto-ignition temperature:

Product is not selfigniting.

· Explosive properties:

Product does not present an explosion hazard.

· Explosion limits:

Lower:

0.6 Vol %

Upper:

7.5 Vol %

· Vapour pressure at 20 °C:

5 hPa

· Density at 20 °C:

0.94 g/cm³

· Relative density

Not determined.

Vapour densityEvaporation rate

Not determined. Not determined.

· Solubility in / Miscibility with

water:

Not miscible or difficult to mix.

· Partition coefficient: n-octanol/water:

Not determined.

· Viscosity:

Dynamic: Kinematic:

Not determined. Not determined.

· Solvent content:

Organic solvents:

51.0 %

Solids content:

18.0 %

(Contd. on page 7)

Trade name: JOHA Siccativ-Drying agent

(Contd. of page 6)

· 9.2 Other information

No further relevant information available.

SECTION 10: Stability and reactivity

- 10.1 Reactivity No further relevant information available.
- 10.2 Chemical stability
- Thermal decomposition / conditions to be avoided:

No decomposition if used according to specifications.

- · 10.3 Possibility of hazardous reactions No dangerous reactions known.
- 10.4 Conditions to avoid No further relevant information available.
- 10.5 Incompatible materials: No further relevant information available.
- · 10.6 Hazardous decomposition products: No dangerous decomposition products known.

SECTION 11: Toxicological information

- · 11.1 Information on toxicological effects
- · Acute toxicity Based on available data, the classification criteria are not met.

•				
· LD/LC50 values relevant for classification:				
64742-95-6 Solvent naphtha (petroleum), light arom.				
LD50	>6800 mg/kg (rat)			
LD50	>3400 mg/kg (rab)			
LC50/4 h	>10.2 mg/l (rat)			
64742-48-9 Naphtha (petroleum), hydrotreated heavy				
LD50	>5000 mg/kg (rat)			
LD50	>3000 mg/kg (rab)			
95-63-6 1,2,4-trimethylbenzene				
LD50	5000 mg/kg (rat)			
103-65-1 propylbenzene				
LD50	6040 mg/kg (rat)			
	Solvent D50 D50 C50/4 h Naphtha D50 D50 4-trimet D50 copylben			

- · Primary irritant effect:
- · Skin corrosion/irritation

Causes skin irritation.

· Serious eye damage/irritation

Causes serious eye irritation.

· Respiratory or skin sensitisation

Based on available data, the classification criteria are not met.

- · CMR effects (carcinogenity, mutagenicity and toxicity for reproduction)
- · Germ cell mutagenicity Based on available data, the classification criteria are not met.
- · Carcinogenicity Based on available data, the classification criteria are not met.
- · Reproductive toxicity Based on available data, the classification criteria are not met.
- STOT-single exposure

May cause respiratory irritation. May cause drowsiness or dizziness.

- · STOT-repeated exposure Based on available data, the classification criteria are not met.
- · Aspiration hazard Based on available data, the classification criteria are not met.

__

Trade name: JOHA Siccativ-Drying agent

(Contd. of page 7)

SECTION 12: Ecological information

- · 12.1 Toxicity
- · Aquatic toxicity: No further relevant information available.
- 12.2 Persistence and degradability No further relevant information available.
- 12.3 Bioaccumulative potential No further relevant information available.
- 12.4 Mobility in soil No further relevant information available.
- · Ecotoxical effects:
- · Remark: Toxic for fish
- · Additional ecological information:
- · General notes:

Water hazard class 3 (German Regulation) (Self-assessment): extremely hazardous for water

Do not allow product to reach ground water, water course or sewage system, even in small quantities.

Danger to drinking water if even extremely small quantities leak into the ground.

Also poisonous for fish and plankton in water bodies.

Toxic for aquatic organisms

- · 12.5 Results of PBT and vPvB assessment
- · PBT: Not applicable.
- · vPvB: Not applicable.
- 12.6 Other adverse effects No further relevant information available.

SECTION 13: Disposal considerations

- · 13.1 Waste treatment methods
- · Recommendation

Must not be disposed together with household garbage. Do not allow product to reach sewage system.

- · Uncleaned packaging:
- · Recommendation: Disposal must be made according to official regulations.

SECTION 14: Transport information

· 14.1 UN-Number	
· ADR, IMDG, IATA	UN1263
· 14.2 UN proper shipping name	
· ADR	1263 PAINT RELATED MATERIAL
· IMDG	PAINT RELATED MATERIAL, MARINE
	POLLUTANT
· IATA	PAINT RELATED MATERIAL

- · 14.3 Transport hazard class(es)
- · ADR, IATA



· Class 3 Flammable liquids.

(Contd. on page 9)



Trade name: JOHA Siccativ-Drying agent

(Contd. of page 8) · Label 3 · IMDG · Class 3 Flammable liquids. · 14.4 Packing group · ADR, IATA Ш · 14.5 Environmental hazards: · Marine pollutant: Yes · 14.6 Special precautions for user Warning: Flammable liquids. · 14.7 Transport in bulk according to Annex II of Marpol and the IBC Code Not applicable. · Transport/Additional information: Limited quantities (LQ) 5L Excepted quantities (EQ) Code: E1 Maximum net quantity per inner packaging: Maximum net quantity per outer packaging: 1000 ml · UN "Model Regulation": UN 1263 PAINT RELATED MATERIAL, 3, III

SECTION 15: Regulatory information

- · 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture
- · Labelling according to Regulation (EC) No 1272/2008

The product is classified and labelled according to the CLP regulation.

· Hazard pictograms







GHS02 GHS07 GHS09

- · Signal word Warning
- · Hazard-determining components of labelling:

Solvent naphtha (petroleum), light arom.

· Hazard statements

H226 Flammable liquid and vapour.

H315 Causes skin irritation.

H319 Causes serious eye irritation.

H335-H336 May cause respiratory irritation. May cause drowsiness or dizziness.

H411 Toxic to aquatic life with long lasting effects.

Precautionary statements

P101 If medical advice is needed, have product container or label at hand.

(Contd. on page 10)



Safety data sheet according to 1907/2006/EC, Article 31

Printing date 21.03.2017 Version number 4 Revision: 21.03.2017

Trade name: JOHA Siccativ-Drying agent

(Contd. of page 9)

P102 Keep out of reach of children.

P103 Read label before use.

P210 Keep away from heat, hot surfaces, sparks, open flames and other

ignition sources. No smoking.

P241 Use explosion-proof electrical/ventilating/lighting equipment.

P303+P361+P353 IF ON SKIN (or hair): Take off immediately all contaminated clothing.

Rinse skin with water/shower.

P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove

contact lenses, if present and easy to do. Continue rinsing.

P405 Store locked up.

P501 Dispose of contents/container in accordance with local/regional/national/

international regulations.

- · Directive 2012/18/EU
- · Named dangerous substances ANNEX I None of the ingredients is listed.
- · Seveso category

E2 Hazardous to the Aquatic Environment

P5c FLAMMABLE LIQUIDS

- · Qualifying quantity (tonnes) for the application of lower-tier requirements 200 t
- · Qualifying quantity (tonnes) for the application of upper-tier requirements 500 t
- · REGULATION (EC) No 1907/2006 ANNEX XVII Conditions of restriction: 3
- · National regulations:
- · Waterhazard class:

Water hazard class 3 (Self-assessment): extremely hazardous for water.

· 15.2 Chemical safety assessment:

A Chemical Safety Assessment has not been carried out.

SECTION 16: Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

· Relevant phrases

H226 Flammable liquid and vapour.

H304 May be fatal if swallowed and enters airways.

H315 Causes skin irritation.

H319 Causes serious eye irritation.

H332 Harmful if inhaled.

H335 May cause respiratory irritation.

H336 May cause drowsiness or dizziness.

H411 Toxic to aquatic life with long lasting effects.

- · Department issuing SDS: Abteilung Umweltschutz
- · Contact: Hr. Hammerl
- · Abbreviations and acronyms:

ADR: Accord européen sur le transport des marchandises dangereuses par Route (European Agreement concerning the International Carriage of Dangerous Goods by Road)

IMDG: International Maritime Code for Dangerous Goods

IATA: International Air Transport Association

GHS: Globally Harmonised System of Classification and Labelling of Chemicals

EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society)

LC50: Lethal concentration, 50 percent

LD50: Lethal dose, 50 percent

PBT: Persistent, Bioaccumulative and Toxic vPvB: very Persistent and very Bioaccumulative

(Contd. on page 11)

Page 11/11



Version number 4 Revision: 21.03.2017

Trade name: JOHA Siccativ-Drying agent

(Contd. of page 10)

Flam. Liq. 3: Flammable liquids – Category 3
Acute Tox. 4: Acute toxicity – Category 4
Skin Irrit. 2: Skin corrosion/irritation – Category 2
Eye Irrit. 2: Serious eye damage/eye irritation – Category 2
STOT SE 3: Specific target organ toxicity (single exposure) – Category 3
Asp. Tox. 1: Aspiration hazard – Category 1
Aquatic Chronic 2: Hazardous to the aquatic environment - long-term aquatic hazard – Category 2

* Data compared to the previous version altered.