Revision: 21.03.2017



## Safety data sheet according to 1907/2006/EC, Article 31

Printing date 21.03.2017

Version number 3

## SECTION 1: Identification of the substance/mixture and of the company/undertaking

- · 1.1 Product identifier
- · Trade name: JOHA Spirit varnish, silky, color varnish
- · Article number:

1421 yellow, 1422 golden yellow, 1423 red, 1424 brown, 1425 amber, 1426 golden brown, 1427 red brown,

- 1428 black
- 1.2 Relevant identified uses of the substance or mixture and uses advised against No further relevant information available.
- · Application of the substance / the mixture For laquering a instrument.
- · 1.3 Details of the supplier of the safety data sheet
- · Manufacturer/Supplier:

Hammerl GmbH & Co. KG Geigenlacke / Violin varnishes Hauptstraße 18 91083 Baiersdorf Phone +49 (0)9133 2330 Fax +49 (0)9133 5171 e-mail joha@hammerl.com

· 1.4 Emergency telephone number:

Giftinformationszentrale Universitätsklinikum Mainz

International

24h Emergency number in German and English

Phone: +49 6131 19240

#### **SECTION 2: Hazards identification**

- · 2.1 Classification of the substance or mixture
- Classification according to Regulation (EC) No 1272/2008



GHS02 flame

Flam. Liq. 2 H225 Highly flammable liquid and vapour.



GHS07

Acute Tox. 4 H302 Harmful if swallowed.

- · 2.2 Label elements
- · Labelling according to Regulation (EC) No 1272/2008

The product is classified and labelled according to the CLP regulation.

Hazard pictograms





GHS02 GHS07

- · Signal word Danger
- · Hazard statements

H225 Highly flammable liquid and vapour.

H302 Harmful if swallowed.

(Contd. on page 2)



# Safety data sheet according to 1907/2006/EC, Article 31

Printing date 21.03.2017 Version number 3 Revision: 21.03.2017

### Trade name: JOHA Spirit varnish, silky, color varnish

(Contd. of page 1)

#### · Precautionary statements

P101 If medical advice is needed, have product container or label at hand.

P102 Keep out of reach of children.

P103 Read label before use.

P210 Keep away from heat, hot surfaces, sparks, open flames and other

ignition sources. No smoking.

P241 Use explosion-proof electrical/ventilating/lighting equipment.

P280 Wear protective gloves/protective clothing/eye protection/face protection. P303+P361+P353 IF ON SKIN (or hair): Take off immediately all contaminated clothing.

Rinse skin with water/shower.

P403+P235 Store in a well-ventilated place. Keep cool.

P501 Dispose of contents/container in accordance with local/regional/national/

international regulations.

#### · Additional information:

42.3 % of the mixture consists of component(s) of unknown toxicity.

- · Labelling of packages where the contents do not exceed 125 ml
- · Hazard pictograms





GHS02 GHS07

- · Signal word Danger
- · Hazard statements

H302 Harmful if swallowed.

#### · Precautionary statements

P101 If medical advice is needed, have product container or label at hand.

P102 Keep out of reach of children.

P103 Read label before use.

P264 Wash thoroughly after handling.

P270 Do not eat, drink or smoke when using this product.

P301+P312 IF SWALLOWED: Call a POISON CENTER/doctor if you feel unwell.

P330 Rinse mouth.

P501 Dispose of contents/container in accordance with local/regional/national/

international regulations.

#### · 2.3 Other hazards

- · Results of PBT and vPvB assessment
- · **PBT:** Not applicable.
- · vPvB: Not applicable.

### **SECTION 3: Composition/information on ingredients**

- · 3.2 Chemical characterisation: Mixtures
- · Description: Mixture of substances listed below with nonhazardous additions.

· Dangerous components:		
CAS: 64-17-5		25-50%
EINECS: 200-578-6	Flam. Liq. 2, H225	
CAS: 107-98-2	1-methoxy-2-propanol	25-50%
EINECS: 203-539-1	Flam. Liq. 3, H226	
CAS: 56-81-5	glycerol	10-25%
EINECS: 200-289-5	substance with a Community workplace exposure limit	

(Contd. on page 3)

Trade name: JOHA Spirit varnish, silky, color varnish

(Contd. of page 2)

· Additional information: For the wording of the listed hazard phrases refer to section 16.

### **SECTION 4: First aid measures**

- · 4.1 Description of first aid measures
- · General information:

Symptoms of poisoning may even occur after several hours; therefore medical observation for at least 48 hours after the accident.

- · After inhalation: Supply fresh air; consult doctor in case of complaints.
- · After skin contact: Generally the product does not irritate the skin.
- · After eye contact: Rinse opened eye for several minutes under running water.
- · After swallowing: Call for a doctor immediately.
- 4.2 Most important symptoms and effects, both acute and delayed No further relevant information available.
- 4.3 Indication of any immediate medical attention and special treatment needed No further relevant information available.

#### **SECTION 5: Firefighting measures**

- · 5.1 Extinguishing media
- · Suitable extinguishing agents:

CO2, powder or water spray. Fight larger fires with water spray or alcohol resistant foam.

- · For safety reasons unsuitable extinguishing agents: Water with full jet
- 5.2 Special hazards arising from the substance or mixture

No further relevant information available.

- · 5.3 Advice for firefighters
- · Protective equipment: No special measures required.

### **SECTION 6: Accidental release measures**

- 6.1 Personal precautions, protective equipment and emergency procedures Wear protective equipment. Keep unprotected persons away.
- 6.2 Environmental precautions: Do not allow to enter sewers/ surface or ground water.
- · 6.3 Methods and material for containment and cleaning up:

Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).

Ensure adequate ventilation.

· 6.4 Reference to other sections

See Section 7 for information on safe handling.

See Section 8 for information on personal protection equipment.

See Section 13 for disposal information.

### **SECTION 7: Handling and storage**

- · 7.1 Precautions for safe handling No special measures required.
- · Information about fire and explosion protection:

Keep ignition sources away - Do not smoke.

Protect against electrostatic charges.

(Contd. on page 4)

## Trade name: JOHA Spirit varnish, silky, color varnish

(Contd. of page 3)

- · 7.2 Conditions for safe storage, including any incompatibilities
- · Storage:
- · Requirements to be met by storerooms and receptacles: Store in a cool location.
- · Information about storage in one common storage facility: Not required.
- · Further information about storage conditions:

Keep container tightly sealed.

Store in cool, dry conditions in well sealed receptacles.

· 7.3 Specific end use(s) No further relevant information available.

#### **SECTION 8: Exposure controls/personal protection**

- · Additional information about design of technical facilities: No further data; see item 7.
- · 8.1 Control parameters

· Ingredients with	limit values that	require monitoring	at the workplace:

#### 64-17-5 ethanol

WEL Long-term value: 1920 mg/m<sup>3</sup>, 1000 ppm

#### 107-98-2 1-methoxy-2-propanol

WEL Short-term value: 560 mg/m³, 150 ppm

Long-term value: 375 mg/m³, 100 ppm

Sk

#### 56-81-5 glycerol

WEL Long-term value: 10 mg/m<sup>3</sup>

- · Additional information: The lists valid during the making were used as basis.
- · 8.2 Exposure controls
- · Personal protective equipment:
- · General protective and hygienic measures:

Wash hands before breaks and at the end of work.

- · Respiratory protection: Not required.
- · Protection of hands:

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.

Due to missing tests no recommendation to the glove material can be given for the product/ the preparation/ the chemical mixture.

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

## · Material of gloves

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

#### · Penetration time of glove material

The exact break trough time has to be found out by the manufacturer of the protective gloves and has to be observed.

(Contd. on page 5)

(Contd. of page 4)



Printing date 21.03.2017 Version number 3 Revision: 21.03.2017

Trade name: JOHA Spirit varnish, silky, color varnish

· Eye protection:



Tightly sealed goggles

## **SECTION 9: Physical and chemical properties**

- · 9.1 Information on basic physical and chemical properties
- · General Information

· Appearance:

Form:

Fluid

Colour:

According to product specification

· Odour:

Characteristic

· Odour threshold:

Not determined.

· pH-value:

Not determined.

· Change in condition

Melting point/freezing point:

Undetermined.

Initial boiling point and boiling range: 78 °C

· Flash point:

13 °C

· Flammability (solid, gas):

Not applicable.

Not determined.

· Ignition temperature:

270 °C

Decomposition temperature:
 Auto-ignition temperature:

Product is not selfigniting.

· Explosive properties:

Product is not explosive. However, formation of

explosive air/vapour mixtures are possible.

· Explosion limits:

Lower:

2.3 Vol %

Upper:

20.0 Vol %

· Vapour pressure at 20 °C:

59 hPa

· Density:

Not determined.

Relative density

Not determined.

Vapour density

Not determined.

· Evaporation rate

Not determined.

· Solubility in / Miscibility with

water:

Not miscible or difficult to mix.

· Partition coefficient: n-octanol/water:

Not determined.

· Viscosity:

Dynamic: Kinematic:

Not determined. Not determined.

· Solvent content:

Organic solvents:

82.1 %

Solids content:

15.6 %

(Contd. on page 6)

Trade name: JOHA Spirit varnish, silky, color varnish

(Contd. of page 5)

· 9.2 Other information

No further relevant information available.

## **SECTION 10: Stability and reactivity**

- 10.1 Reactivity No further relevant information available.
- · 10.2 Chemical stability
- Thermal decomposition / conditions to be avoided:

No decomposition if used according to specifications.

- · 10.3 Possibility of hazardous reactions No dangerous reactions known.
- 10.4 Conditions to avoid No further relevant information available.
- 10.5 Incompatible materials: No further relevant information available.
- · 10.6 Hazardous decomposition products: No dangerous decomposition products known.

## **SECTION 11: Toxicological information**

- · 11.1 Information on toxicological effects
- · Acute toxicity

Harmful if swallowed.

	· LD/LC50 values relevant for classification:			
	Oral	LD50	1200 mg/kg (rat)	
	64-17-5 ethanol			
	Oral	LD50	3450 mg/kg (mouse)	
			7060 mg/kg (rat)	
			6300 mg/kg (rabbit)	
	Dermal	LD50	> 2000 mg/kg (rat)	
	Inhalative	LC50/4 h	20000 mg/l (rat)	
	107-98-2 1-methoxy-2-propanol			
	Oral	LD50	4016 mg/kg (rat)	
	Dermal	LD50	13000 mg/kg (rabbit)	
	56-81-5 glycerol			
	Oral	LD50	12600 mg/kg (rat)	
_	D.:	:44 -ff-	-1	

- · Primary irritant effect:
- · Skin corrosion/irritation Based on available data, the classification criteria are not met.
- · Serious eye damage/irritation

Based on available data, the classification criteria are not met.

· Respiratory or skin sensitisation

Based on available data, the classification criteria are not met.

- · CMR effects (carcinogenity, mutagenicity and toxicity for reproduction)
- · Germ cell mutagenicity Based on available data, the classification criteria are not met.
- · Carcinogenicity Based on available data, the classification criteria are not met.
- · Reproductive toxicity Based on available data, the classification criteria are not met.
- · STOT-single exposure Based on available data, the classification criteria are not met.
- · STOT-repeated exposure Based on available data, the classification criteria are not met.
- · Aspiration hazard Based on available data, the classification criteria are not met.

GB

Trade name: JOHA Spirit varnish, silky, color varnish

(Contd. of page 6)

## **SECTION 12: Ecological information**

- · 12.1 Toxicity
- · Aquatic toxicity: No further relevant information available.

· Type of tes	t Effective concentration Method Assessment				
64-17-5 ethanol					
EC50 (48h)	9268 mg/l (daphnia magna)				
LC50 (48h)	8140 mg/l (gol)				
LC50 (24h)	> 100 mg/l (daphnia magna)				
EC5 (16h)	6500 mg/l (Pseudomonas Putita)				
107-98-2 1-methoxy-2-propanol					
LC50 (48h)	23300 mg/l (daphnia magna)				
LC50 (96h)	> 6800 mg/l (gol)				
EC50 (3h)	> 1000 mg/l (Pseudomonas Putita)				

- 12.2 Persistence and degradability No further relevant information available.
- 12.3 Bioaccumulative potential No further relevant information available.
- 12.4 Mobility in soil No further relevant information available.
- · Additional ecological information:
- · General notes:

Water hazard class 1 (German Regulation) (Self-assessment): slightly hazardous for water Do not allow undiluted product or large quantities of it to reach ground water, water course or sewage system.

- · 12.5 Results of PBT and vPvB assessment
- · **PBT**: Not applicable.
- · vPvB: Not applicable.
- 12.6 Other adverse effects No further relevant information available.

## **SECTION 13: Disposal considerations**

- · 13.1 Waste treatment methods
- · Recommendation

Must not be disposed together with household garbage. Do not allow product to reach sewage system.

- · Uncleaned packaging:
- · Recommendation: Disposal must be made according to official regulations.

SECTION 14: Transport information		
· 14.1 UN-Number		
· ADR, IMDG, IATA	UN1170	
· 14.2 UN proper shipping name		
· ADR	1170 ETHANOL (ETHYL ALCOHOL)	
· IMDG	ETHANOL (ETHYL ALCOHOL)	
· IATA	ETHANOL	
	(Contd. on page	



## Trade name: JOHA Spirit varnish, silky, color varnish

(Contd. of page 7)

· 14.3 Transport	hazard class	(es)	
------------------	--------------	------	--

· ADR, IMDG, IATA



· Class 3 Flammable liquids.

· Label 3

· 14.4 Packing group

· ADR, IMDG, IATA

· 14.5 Environmental hazards:

· Marine pollutant: No

• 14.6 Special precautions for user Warning: Flammable liquids.

Danger code (Kemler): 33
EMS Number: F-E,S-D
Stowage Category A

· 14.7 Transport in bulk according to Annex

II of Marpol and the IBC Code Not applicable.

· Transport/Additional information:

ADR

· Limited quantities (LQ) 1L

• Excepted quantities (EQ) Code: E2

Maximum net quantity per inner packaging:

30 ml

Maximum net quantity per outer packaging:

500 ml

Transport categoryTunnel restriction codeD/E

· IMDG

· Limited quantities (LQ) 1L

· Excepted quantities (EQ) Code: E2

Maximum net quantity per inner packaging:

30 ml

Maximum net quantity per outer packaging:

500 ml

· UN "Model Regulation": UN 1170 ETHANOL (ETHYL ALCOHOL), 3,

Ш

## **SECTION 15: Regulatory information**

· 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

· Labelling according to Regulation (EC) No 1272/2008

The product is classified and labelled according to the CLP regulation.

(Contd. on page 9)



## Trade name: JOHA Spirit varnish, silky, color varnish

(Contd. of page 8)

#### · Hazard pictograms





GHS02 GHS07

- · Signal word Danger
- · Hazard statements

H225 Highly flammable liquid and vapour.

H302 Harmful if swallowed.

#### · Precautionary statements

P101 If medical advice is needed, have product container or label at hand.

P102 Keep out of reach of children.

P103 Read label before use.

P210 Keep away from heat, hot surfaces, sparks, open flames and other

ignition sources. No smoking.

P241 Use explosion-proof electrical/ventilating/lighting equipment.

P280 Wear protective gloves/protective clothing/eye protection/face protection. P303+P361+P353 IF ON SKIN (or hair): Take off immediately all contaminated clothing.

Rinse skin with water/shower.

P403+P235 Store in a well-ventilated place. Keep cool.

P501 Dispose of contents/container in accordance with local/regional/national/

international regulations.

- · Directive 2012/18/EU
- · Named dangerous substances ANNEX I None of the ingredients is listed.
- · Seveso category P5c FLAMMABLE LIQUIDS
- · Qualifying quantity (tonnes) for the application of lower-tier requirements 5,000 t
- · Qualifying quantity (tonnes) for the application of upper-tier requirements 50,000 t
- · REGULATION (EC) No 1907/2006 ANNEX XVII Conditions of restriction: 3
- · National regulations:
- · Waterhazard class: Water hazard class 1 (Self-assessment): slightly hazardous for water.
- · 15.2 Chemical safety assessment:

A Chemical Safety Assessment has not been carried out.

#### **SECTION 16: Other information**

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

## · Relevant phrases

H225 Highly flammable liquid and vapour.

H226 Flammable liquid and vapour.

- · Department issuing SDS: Abteilung Umweltschutz
- · Contact: Hr. Hammerl
- · Abbreviations and acronyms:

RID: Règlement international concernant le transport des marchandises dangereuses par chemin de fer (Regulations Concerning the International Transport of Dangerous Goods by Rail)

IATA-DGR: Dangerous Goods Regulations by the "International Air Transport Association" (IATA)

ICAO: International Civil Aviation Organisation

ICAO-TI: Technical Instructions by the "International Civil Aviation Organisation" (ICAO)

ADR: Accord européen sur le transport des marchandises dangereuses par Route (European Agreement concerning the International Carriage of Dangerous Goods by Road)

IMDG: International Maritime Code for Dangerous Goods

(Contd. on page 10)



# Safety data sheet according to 1907/2006/EC, Article 31

Printing date 21.03.2017 Version number 3 Revision: 21.03.2017

## Trade name: JOHA Spirit varnish, silky, color varnish

(Contd. of page 9)

IATA: International Air Transport Association

GHS: Globally Harmonised System of Classification and Labelling of Chemicals EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society)

LC50: Lethal concentration, 50 percent

LD50: Lethal dose, 50 percent

PBT: Persistent, Bioaccumulative and Toxic vPvB: very Persistent and very Bioaccumulative Flam. Liq. 2: Flammable liquids – Category 2 Flam. Liq. 3: Flammable liquids – Category 3 Acute Tox. 4: Acute toxicity – Category 4

\* Data compared to the previous version altered.

GB ·